

TRIPLE POINTTM When you're serious about security



For commercial and industrial applications Power Stations Shipping Terminals Refineries Airports Defence Facilities

TRIPLE POINT[™] is an extremely robust barrier manufactured from solid steel components with an aggressive press formed triple point top on each picket.

TRIPLE POINT[™] is used extensively throughout the UK and Europe in applications requiring extreme security including power stations, defence facilities, airports etc.

TRIPLE POINT^m has the unique ability to allow panels to be installed on sloping ground, following all contours up to 15°.

TRIPLE POINT[™] is a complete modular system which is extremely simple to install. All individual components are hot dip galvanized prior to site assembly giving this system superior durability.

SPECIFICATIONS

Panel

Description

TRIPLE POINT[™] comprises of roll formed pickets with an aggressive triple point spear top fixed to a top and bottom horizontal rail using tamper proof fasteners.

Finish

Standard finish is Hot Dip Galvanised with an option of polyester powder coating.

Dimensions

Height:	2350mm or 2950mm
Width:	2720mm
Picket:	70 x 18 x 3 x 2350 or 2950mm
Rails:	50 x 50 x 6 x 2720mm Steel Angle

Post

Description

The posts are supplied complete ready to install with slotted holes for fish plate assembly.

Finish

Standard finish is Hot Dip Galvanised with an option of polyester powder coating.

Dimensions

Length: Size: Post centres: 3200 or 3800mm 100 x 45 TFB (7.2kg/metre) 2750mm

Specification Clauses

To be read with preliminaries and general conditions

Steel picket security fence/gates

- Manufacturer & Ref: JAGFENCE SYSTEMS Tel: 1800 628 785. **TRIPLE POINT**[™] palisade
- Height:
 - Pickets: 70 x 18 x 3mm roll formed steel W section at 154mm centres with triple point spear top
- Rails: 50 x 50 x 6mm steel angle
- Post: 100 x 45 TFB (7.2kg/metre)
- Fish Plate: 40 x 6mm steel plate
- Coating: All components to be Hot Dip Galvanised (minimum 500 gsm)
- Footings: Set posts in 20 mpa concrete footing 250mm diameter x 900mm deep
- Post Centres: 2750mm
- Fixings: Picket to Rail M8 x 20 T-bolt with flat washer & shear nut. Rail to Fish Plate M12 Bolt with flat washer & shear nut.
- Bottom of fence to be installed 50mm above ground level

Variations

In addition to the standard posts, rails and pickets, many variations are available including:

- · Alternative posts and rail sections
- Pickets with cranked tops
- Extensions for barb, razor or electric toppings

Other services

- · Gate manufacture (swing and sliding)
- Site deliveries



Distributed by:



All information correct at time of going to print. We reserve the right to alter specifications without notice.